



# HF64

PRO HF HORN



|                    |  |
|--------------------|--|
| <b>Description</b> | 1-inch/1.4 inch Throat Adaptor.60° x 40° Constant Directivity Coverage. Thick Aluminum Body for best heat dissipation in conjunction to Neodimium Compression Drivers. |
|--------------------|--|

- |                 |   |
|-----------------|---|
| <b>Features</b> | <ul style="list-style-type: none"><li>› 1-inch/1.4 inch Throat Adaptor</li><li>› 60° x 40° Constant Directivity Coverage</li><li>› Loading down to 500 Hz</li><li>› Thick Aluminum Body for best heat dissipation in conjunction to Neodimium Compression Drivers</li><li>› Perfectly Controlled Dispersion</li></ul> |
|-----------------|---|

|                    |               |
|--------------------|---------------|
| <b>Part Number</b> | 13133046 HF64 |
|--------------------|---------------|



# HF64

PRO HF HORN

| TECHNICAL SPECIFICATIONS |                           |  |
|--------------------------|---------------------------|--|
| General specifications   | Throat Diameter           | 25-36 mm / 1.0-1.4 inch                |
|                          | Horizontal coverage angle | 60°                                    |
|                          | Vertical coverage angle   | 40°                                    |
|                          | Cut-off Frequency         | 500 Hz                                 |
|                          | Material                  | Aluminum                               |
| Mounting information     | Overall height            | 250 mm / 9.84 inches                   |
|                          | Overall width             | 25 mm / 0.98 inches                    |
|                          | Overall depth             | 179 mm / 7.05 inches                   |
|                          | Baffle Cut-out height     | 205 mm / 8.07 inches                   |
|                          | Baffle Cut-out width      | 205 mm / 8.07 inches                   |
|                          | Mounting                  | 4 x 7 mm holes, interaxes 101 mm/76 mm |
| Standard compliance      | Safety agency             | CE compliant                           |
| Size / Weight            | Height                    | 186 mm / 7.32 inches                   |
|                          | Diameter                  | 250 mm / 9.84 inches                   |
|                          | Weight                    | 1.48 kg / 3.26 lbs                     |

Line Art 2D

